



### **Additional Information about UMS radial engine Installation:**

The fuel line between carburetor and tank inlet should not be longer than 200mm to ensure full power. The tank has to be installed on same level ( not lower , not higher) like the carburetor to ensure best possible fuel-flow , if this is not possible to achieve in your model , you should use a fuel pump.

### **Zusatzinformationen zur Installation von UMS Sternmotoren**

Die Kraftstoffleitung zwischen Vergaser und Tankanschluß sollte nicht länger als 200mm sein um die optimale Leistung zu gewährleisten. Der Tank sollte auf der gleichen Höhe wie der Vergaser angeordnet sein ( nicht höher, nicht tiefer) um die optimale Kraftstoffversorgung zu gewährleisten. Falls dies in Ihrem Modell nicht möglich ist , verwenden Sie bitte eine Kraftstoffpumpe.

Tomahawk Aviation GmbH Carl-Benz-Str. 7 , 89284 Pfaffenhofen a.d. Roth , Germany  
Registergericht: HRB17672, Amtsgericht Memmingen UST-ID: DE311764140  
Geschäftsführer: Andreas Och , Thomas Höchsmann

Bankverbindung: Hamburger Sparkasse IBAN: DE58 2005 0550 1265 2102 43 BIC: HASPDEHHXXX